



WH5500E Petrol Generator

SPECIFICATIONS

| | |
|---------------------------|--|
| Rated frequency: | 50 Hz |
| Rated voltage: | 230 V |
| Rated output power: | 4.0 kW |
| Max. output power: | 4.5 kW (4.5 KVA) |
| DC output: | 12 V, 8 A |
| Noise level dB @ 7m: | 70-74 (no load – full load) |
| Fuel tank: | 22 litres |
| Overall dimensions: | 630 x 535 x 635 mm (L x W x H) |
| Net weight: | 76.5kg |
| Engine type: | Single cylinder, 4 stroke, air cooled, OHV gasoline engine |
| Displacement: | 337 cc |
| Compression ratio: | 8.5:1 |
| Rated power: | 11.0 Hp |
| Rated rotation speed: | 3600 rpm |
| Starting system: | Electric starter |
| Fuel type: | Automotive unleaded gasoline |
| Lube oil brand: | SAE10W30 (above cc grade) |
| Low oil alarm system: | Yes |
| Wheels and handle: | Yes |
| Recommended battery: | NP18-12B (12v, 17.2Ah) (Battery not supplied) |
| Full tank operating time: | 13 hours (at ½ load) |
| Earth leakage protection: | Yes |
| Alternator: | Integrated circuit |
| AVR: | Fitted |

